

ADLER Varicolor

Version number: 13.0

Revision: 2022-05-31
Date of issue: 2022-05-31:

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **ADLER Varicolor** **4117a:**
Different colours

Product number 4117009016 ff

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Coating material for commercial or consumer end-uses.

Uses advised against Any use not listed above.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

ADLER-Werk Lackfabrik Johann Berghofer GmbH & Co KG
Bergwerkstraße 22
A-6130 Schwaz
Austria

Telephone: +4352426922713
e-mail: sdb-info@adler-lacke.com

Further information obtainable from: sdb-info@adler-lacke.com

Telephone
+43 5242 6922-713
Mon - Thu 07:00 AM - 04:25 PM
Fri 07:00 AM - 12:15 PM

1.4 Emergency telephone number

Country	Name	Telephone
United Kingdom	Guy's & St Thomas' Poisons Unit	+44 (0)20 7188 0100

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

This mixture does not meet the criteria for classification.

2.2 Label elements

Labelling

- Signal word not required

- Pictograms not required

- Supplemental hazard information

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, Reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

EUH210 Safety data sheet available on request.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

Keep out of reach of children and do not empty into the drains. Dispose remainders properly (collection of hazardous waste, disposal companies). Empty containers must be entered into the recycling system. The usual safety precautions must be observed during processing of the product.

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Water-based polymer dispersion with pigments and other additives.

Name of substance	Identifier	Wt%	Classification acc. to GHS
titanium dioxide	CAS No 13463-67-7	10 – < 25	Carc. 2 / H351
1,2-benzisothiazol-3(2H)-one	CAS No 2634-33-5	< 0.05	Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Eye Dam. 1 / H318 Skin Sens. 1 / H317 Aquatic Acute 1 / H400
Reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	CAS No 55965-84-9	< 0.05	Acute Tox. 3 / H301 Acute Tox. 2 / H310 Acute Tox. 2 / H330 Skin Corr. 1C / H314 Eye Dam. 1 / H318 Skin Sens. 1A / H317 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410

Name of substance	Specific Conc. Limits	M-Factors	ATE	Exposure route
1,2-benzisothiazol-3(2H)-one	Skin Sens. 1; H317: C ≥ 0.05 %	M-factor (acute) = 10	670 mg/kg	oral
Reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	Skin Corr. 1C; H314: C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.002 %	M-factor (acute) = 100 M-factor (chronic) = 100	100 mg/kg 50 mg/kg 0.5 mg/l/4h 0.05 mg/l/4h	oral dermal inhalation: vapour inhalation: dust/ mist

For full text of abbreviations: see SECTION 16. This mixture contains ≥ 1% titanium dioxide (CAS 13463-67-7). The Annex VI classification of Titanium dioxide does not apply to this mixture according to its Note 10.

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth. Take off immediately all contaminated clothing. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

ADLER Varicolor

Version number: 13.0

Revision: 2022-05-31
Date of issue: 2022-05-31:

Following inhalation

Provide fresh air. If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions.

Following skin contact

Take off contaminated clothing. After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. Do not use any solvents or thinners!.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Keep at rest. IF SWALLOWED: Immediately call a doctor.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), BC-powder, Water spray, Alcohol resistant foam, Sand

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Thick smoke may occur in case of a fire. Inhaling the decomposed products may cause serious damage to health. The formation of explosive dust-air-mixtures is possible. Upon contact with air, the vapours may form an explosive mixture. . Combustible.

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety. Provision of sufficient ventilation. Control of dust.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. Dilute with plenty of water.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains, Fill contaminated material in the original container or any other suitable one and dispose it in accordance with point 13.

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feed-stuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Flammability hazards

Keep away from sources of ignition - No smoking.

Control of effects

Do not pierce or burn, even after use. Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. . Close the open container carefully and keep it straight to prevent leakage.

Store in the original container. Storage temperature of 0 °C/32 °F and up to 50 °C/122 °F.

Protect against external exposure, such as

frost

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
GB	titanium dioxide	13463-67-7	WEL		10					i	EH40/2005
GB	titanium dioxide	13463-67-7	WEL		4					r	EH40/2005
GB	propane-1,2-diol	57-55-6	WEL		10					particle	EH40/2005
GB	propane-1,2-diol	57-55-6	WEL	150	474					vp	EH40/2005

Notation

Ceiling-C	ceiling value is a limit value above which exposure should not occur
i	inhalable fraction
particle	as airborne particles
r	respirable fraction
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)
vp	as vapours and particulates

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
1,2-benzisothiazol-3(2H)-one	2634-33-5	DNEL	6.81 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
1,2-benzisothiazol-3(2H)-one	2634-33-5	DNEL	0.966 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9	DNEL	0.02 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
Reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9	DNEL	0.04 mg/m ³	human, inhalatory	worker (industry)	acute - local effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
1,2-benzisothiazol-3(2H)-one	2634-33-5	PNEC	4.03 µg/l	aquatic organisms	freshwater	short-term (single instance)
1,2-benzisothiazol-3(2H)-one	2634-33-5	PNEC	0.403 µg/l	aquatic organisms	marine water	short-term (single instance)
1,2-benzisothiazol-3(2H)-one	2634-33-5	PNEC	1.03 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
1,2-benzisothiazol-3(2H)-one	2634-33-5	PNEC	49.9 µg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
1,2-benzisothiazol-3(2H)-one	2634-33-5	PNEC	4.99 µg/kg	aquatic organisms	marine sediment	short-term (single instance)
1,2-benzisothiazol-3(2H)-one	2634-33-5	PNEC	3 mg/kg	terrestrial organisms	soil	short-term (single instance)
Reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9	PNEC	3.39 µg/l	aquatic organisms	freshwater	short-term (single instance)
Reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9	PNEC	3.39 µg/l	aquatic organisms	marine water	short-term (single instance)
Reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9	PNEC	0.23 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9	PNEC	0.027 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9	PNEC	0.027 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9	PNEC	0.01 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

ADLER Varicolor

Version number: 13.0

Revision: 2022-05-31
Date of issue: 2022-05-31:

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Use safety goggle with side protection (EN 166).

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Use protective gloves made of latex or PVC as spray protection for short-term work. Latex: penetration time $\geq$ 480 min, material strength: 0.5mm / PVC: penetration time > 60 min, material strength: 0.2mm.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

During spraying wear suitable respiratory equipment. Combination filtering device (EN 141). Particulate filter device (EN 143). Type: A-P2 (combined filters against particles and organic gases and vapours, colour code: Brown/White).

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	different colours
Odour	specific type
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	100 °C
Flammability	not relevant
Flash point	not determined
Auto-ignition temperature	not applicable
pH (value)	8 – 9 (20 °C)
Dynamic viscosity	2,300 – 8,000 mPa s

Solubility(ies)

Water solubility	miscible in any proportion
------------------	----------------------------

ADLER Varicolor

Version number: 13.0

Revision: 2022-05-31
Date of issue: 2022-05-31:

Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Vapour pressure	23 hPa at 20 °C
-----------------	-----------------

Density and/or relative density

Density	1.108 – 1.347 g/cm ³ at 20 °C
Relative vapour density	information on this property is not available

Particle characteristics	not relevant (liquid)
--------------------------	-----------------------

Other safety parameters

Explosive properties	Does not apply (see note in chapter 16)
----------------------	---

9.2 Other information

Information with regard to physical hazard classes	hazard classes acc. to GHS (physical hazards): not relevant
--	---

Other safety characteristics

Miscibility	Completely miscible with water.
-------------	---------------------------------

SECTION 10: Stability and reactivity**10.1 Reactivity**

This material is not reactive under normal ambient conditions.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

Oxidisers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

This mixture does not meet the criteria for classification.

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
1,2-benzisothiazol-3(2H)-one	2634-33-5	oral	670 mg/kg
Reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9	oral	100 mg/kg
Reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9	dermal	50 mg/kg
Reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9	inhalation: vapour	0.5 mg/l/4h
Reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9	inhalation: dust/mist	0.05 mg/l/4h

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Contains 1,2-benzisothiazol-3(2H)-one, Reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

11.2 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste

List of wastes

- Product

08 01 15* aqueous sludges containing paint or varnish containing organic solvents or other hazardous substances

- Packagings

15 01 10* packaging containing residues of or contaminated by hazardous substances

Disposal methods:

Product

Waste production should be avoided or minimised if possible.

Do not empty into the drains. Avoid releasing the product into the environment. Waste, containers must be removed, disposed in a safe way.

Packagings

Waste production should be avoided or minimised if possible.

Packaging waste should be recycled. Burning or landfilling should only be considered if recycling is not feasible.

ADLER Varicolor

Version number: 13.0

Revision: 2022-05-31
Date of issue: 2022-05-31:

Notes on disposal:

Product

Disposal of this product and its dissolutions and by-products must be carried out in accordance with the environmental protection requirements and waste disposal laws as well as the requirements of the local authorities at all times. Excess must be handed over, disposed to a recognised waste disposal company (disposal company/recycling company).

Packagings

With the aid of the information provided in this safety data sheet, the responsible authorities must be consulted regarding classification of empty containers, packaging. Empty containers should be disposed, recycled according to type. Licenced containers, packaging can be disposed free of charge via system partners, where applicable. Containers with residual contents must be disposed in accordance with local and national legal provisions.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

- | | |
|---|---|
| 14.1 UN number or ID number | not subject to transport regulations |
| 14.2 UN proper shipping name | not relevant |
| 14.3 Transport hazard class(es) | none |
| 14.4 Packing group | not assigned |
| 14.5 Environmental hazards | non-environmentally hazardous acc. to the dangerous goods regulations |
| 14.6 Special precautions for user | |
| There is no additional information. | |
| 14.7 Maritime transport in bulk according to IMO instruments | |
| The cargo is not intended to be carried in bulk. | |

Information for each of the UN Model Regulations

International Maritime Dangerous Goods Code (IMDG) - Additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- Relevant provisions of the European Union (EU)**
- Seveso Directive**

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
	not assigned		

Deco-Paint Directive

VOC content	3.657 % 50 g/l
-------------	-------------------

Industrial Emissions Directive (IED)

VOC content	2.659 % 32.13 g/l
-------------	----------------------

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

Water Framework Directive (WFD)

List of pollutants (WFD)			
Name of substance	CAS No	Listed in	Remarks
titanium dioxide		a)	
titanium dioxide		a)	
Reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)		a)	
Reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)		a)	

Legend

A) Indicative list of the main pollutants

Regulation on drug precursors

none of the ingredients are listed

Regulation on persistent organic pollutants (POP)

None of the ingredients are listed.

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

ADLER Varicolor

Version number: 13.0

Revision: 2022-05-31
Date of issue: 2022-05-31:

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
ATE	Acute Toxicity Estimate
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-licence/)
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
M-factor	Means a multiplying factor. It is applied to the concentration of a substance classified as hazardous to the aquatic environment acute category 1 or chronic category 1, and is used to derive by the summation method the classification of a mixture in which the substance is present
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitisation

ADLER Varicolor

Version number: 13.0

Revision: 2022-05-31
Date of issue: 2022-05-31:

Abbr.	Descriptions of used abbreviations
STEL	Short-term exposure limit
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Note concerning the lower explosion limit of water-thinnable varnishes:

See PTB research report PEx5 200500185, Physical-Technical Federal Agency Braunschweig, September 2005 and report PTB-W-57, February 1994.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.