

ADLER Aqua-Fluid V

8052000210

Special additive for ADLER Pigmocryl NG for industrial and professional use

PRODUCT DESCRIPTION

General

Retarder for the water-based coloured paint system Pigmocryl NG 3200 ff to improve the flow and degassing at elevated ambient temperatures or low humidity.


Application areas



- Additive for Pigmocryl NG for furniture and interior finishing.
- Please observe the relative technical data sheets of the products.


PROCESSING

Instructions for use



- Please stir the product before use.
- Add ADLER Aqua-Fluid V 8052000210 to the paint while stirring.
- The viscosity and good stability of the paint on vertical surfaces are maintained. However, the viscosity of the mixtures with ADLER Aqua-Fluid V 8052000210 may differ from the initial viscosity.
- ADLER Aqua-Fluid V 8052000210 does not affect the storability of the paint.
- Please follow our “**Working guidelines for water-based furniture varnishes**”.

Quantity to be added



5 percent by weight to paint.

We recommend observing a waiting time of approx. 5 min. before processing.

Cleaning the working equipment



With water immediately after use.

ORDERING INFORMATION

Size of trading unit 1 l

FURTHER DETAILS

Durability/storage

At least 1 year in the original sealed containers.

Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).

Safety-related information

Please pay attention to the associated safety data sheet. The current version can be accessed on the Internet at www.adler-lacke.com.

The product is only suitable for industrial and professional use.
