

ADLER Aquafix E

8128 000210


Additive for ADLER Pigmocryl NG for industrial and professional use

PRODUCT DESCRIPTION

General

Colorless, water-based additive for ADLER Pigmocryl NG for use in structures that require high elasticity (such as stairs).

Application area



- For furniture, interior fixtures, wall paneling and wood ceilings.
- For the commercial and industrial painting of stairs.

PROCESSING


Instructions for use



- Please stir the product before use.
- Carefully stir ADLER Aquafix E 8128 000210 into the undiluted paint; then incorporate the required amount of thinner.
- Mixed paints must be processed as specified in the corresponding technical data sheet.
- ADLER Aquafix E 8128 000210 leads to a noticeable increase in the gloss level of the finished paintwork.
- The processing properties of ADLER Pigmocryl NG 3201 ff are maintained..

Quantity to be added

20 per cent by weight to paint.



Drying times

(at 23 °C and 50 % rel. humidity)

The drying of the coating systems is not influenced by adding ADLER Aquafix E 8128 000210.


Cleaning the working equipment

With water immediately after use.

To remove dried paint residues we recommend using ADLER Aqua-Cleaner 80080 (diluted 1:1 with water).

ORDERING INFORMATION**Size of trading unit**

4.4 kg

FURTHER DETAILS**Durability/storage**

At least 1 year in the original sealed containers.

Make sure the product is protected against direct sunlight, frost and high temperatures (above 30 °C).

Safety-related information

Please pay attention to the associated safety data sheet. The current version can be accessed on the Internet at **www.adler-lacke.com**.

The product is only suitable for industrial and professional use.
