

Mattkonzentrat

4511

Matting concentrate for synthetic resin coatings for DIY, professional and industrial use

PRODUCT DESCRIPTION

Product numbers

4511000210

General

Solvent-based additive for targeted gloss reduction without affecting the fundamental film properties.

Application area

The additive can be used in combination with solvent-based synthetic resin coatings

PROCESSING

Processing instructions



- Please stir and shake the product well before use (1 minute on shaker).
- The temperature of the product and object, and the room temperature must be at least +10 C.
- The gloss level, colour shade, compatibility and adhesion to the substrate must be checked by preparing sample areas.
- Mixed paints must be processed as specified in the corresponding technical data sheet.
- Carefully stir Mattkonzentrat (4511) into the undiluted coating; afterwards stir in the required amount of thinner.
- Any change in the processing sequence, environmental conditions, non-observance of instructions or the use of products not listed may have an unfavourable effect on the result. Deviations lead to film and adhesion problems as well as to impairments with regard to weathering and color stability.

Quantity to be added



For interior products: max. 10%

For exterior products: max. 5%

Drying times

(at 23 °C and 50 % rel. humidity)

The drying behaviour of the coating system is not affected by the addition of Mattkonzentrat (4511).

Cleaning the working equipment

8014

With KH-Spritzverdünner (8014) immediately after use.

To remove dried product residues we recommend using Clean Abbeizer-Express (8313).

ORDERING INFORMATION**Size of trading unit**

11

FURTHER DETAILS**Durability / storage**

Min. 5 year(s) in the original sealed containers.

Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).

Immediately seal the container to prevent humidity from penetrating.

Safety information

Further information on the subject of safety during transport, storage and handling as well as disposal can be found in the relevant safety data sheet. The current version can be accessed on the Internet at www.adler-lacke.com.
