


## ADLER Pigmofix RF

90695



### Product description

Additive for two-component polyurethane pigmented varnishes, solvent based, for receiving an excellent ring-test stability and for increasing the nail-hardness. The degree of gloss of the received surface is not influenced.

### Fields of application

As additive for ADLER Pigmopur 24005 ff for the last and final coating for increasing the ring-test stability and the scratch-resistance.

### Mixing ratio

The **mixing ratio** to ADLER Pigmopur 24005 ff is **10 %**, calculated on the varnish (without quantity of hardener and thinner).

#### Stir well before use!

#### Agitate well!

We recommend to mix ADLER Pigmofix RF 90695 together with the corresponding quantity of hardener into the varnish.

### Particular indications

ADLER Pigmofix RF 90695 does not influence the drying time of ADLER Pigmopur 24005 ff. The excellent ring-stability is reached after 1 – 2 days.

After a careful grinding a touch-up coating is possible.

Please refer to our "Guidelines for PUR-varnishes" and the Technical data sheet for ADLER Pigmopur 24005 ff as well as to the safety data sheet.

### Drum sizes

0,4 kg

### Storage life

1 year in original closed drums

### Storage

Cold, but frost-free

12-09 (replaces 05-06 )

ADLER-Werk Lackfabrik, A-6130 Schwaz  
Fon: 0043/5242/6922-190, Fax: 0043/5242/6922-309, Mail: [info@adler-lacke.com](mailto:info@adler-lacke.com)